Asian Journal of Applied Science and Technology (AJAST)

(Peer Reviewed Quarterly International Journal) Volume 3, Issue 1, Pages 280-287, Jan-March 2019

Effectualness of PID Controller for Z-Source Ultrasparse Matrix Converter

Ida Sylvania.V[1] & D.Dan Prakash[2]

[1]*M.E (Power Electronics and Drives), Department of (Electrical and Electronics), CSI College of Engineering, Ketti, The Nilgiris.*
[2]*Assistant Professor, Department of (Electrical and Electronics), CSI College of Engineering, Ketti, The Nilgiris.*

Article Received: 30 August 2018 Article Accepted: 29 December 2018 Article Published: 27 March 2019

ABSTRACT

Z-source systems are utilized to upgrade the boosting capacity of network converters. This work focuses on surged Z-source ultrasparse matrix converter (ZSUSMC), where the Z-source organizes is put between the three-switch input rectifier and the six-switch yield inverter arrange. Two space vector balance plans, with and without a zero state in the rectifier arrange adjustment, are introduced and their favorable circumstances and inconveniences are talked about. Likewise, confinements forced on the converter task in buck mode, which emerges from the unidirectional nature of the ultrasparse grid converter, are examined and an answer is proposed for balancing those constraints. Moreover, an ideal exchanging design, which results in the least conceivable number of changes in the exchanging states just as even conveyance of the shoot-through state over the whole control time frame, is proposed. Additionally, regular mode voltages of the converter in all conceivable exchanging designs are determined. The Proportional-Integral (PI) controller has been utilized and commanded the procedure control enterprises for quite a while as it gives the control activity as far as remuneration dependent on present mistake input (corresponding control) just as relying upon past blunder (fundamental control). As the term PI recommends, it includes two separate steady parameters, for example corresponding consistent and vital steady which are balanced so as to get the perfect, unfaltering and quicker reaction and to diminish the enduring state blunder to zero or if nothing else to an extremely little resilience limit. This work expects to display an investigation of the improvement of a dynamic model dependent on speculations of Proportional Integral Derivative (PID) control and advancement to structure voltage controller circuit. Closed circle techniques utilizing fluffy rationale control and nonlinear PID control are proposed to improve the execution of the ZSIMC within the sight of aggravations on the info voltage.

Keywords: Z- Source, Ultra sparse matrix, PI, PID.

1. INTRODUCTION

HIGH number of semiconductor segments, complex control, and low voltage exchange proportion (VTR) are real downsides of direct matrix converters (DMCs). So as to address the issue of high number of semiconductor parts, the ultra sparse matrix converter (USMC) has been proposed. USMC, which is arranged under Indirect Matrix converters (IMCs), utilizes just nine switches and eighteen diodes in its topology. As another favorable position, the mind boggling compensation issue in DMC can be mitigated in the USMC by utilizing the basic zero dc-interface current recompense strategy. So as to address the constrained VTR issue in DMC and IMC, over regulation procedures are proposed before. In spite of some achievement, these systems result in low-quality info flows and yield voltages. Different methodologies, for example, using a stage up transformer at the yield terminals of the framework converter or altering the topology have not gotten much consideration because of extra expenses and unpredictability. Joining Z-source (ZS) systems with MC topologies is viewed as a practical answer for improving the boosting capacity of the MC [5]. An extensive audit of ZS systems utilized with DMC is completed before. Due to the previously mentioned focal points of IMC over DMC, Z-source IMC (ZSIMC) is considered and examined in this work. In existing, ZS organize is proposed to be set between the three-stage input voltage source and the IMC. This course of action acknowledges high VTRs with little ZS parts, yet it builds the expense and diminishes the dependability of the converter because of extra switches in the structure.

CITE THIS ARTICLE: Ida Sylvania.V & D.Dan Prakash, "Effectualness of PID Controller for Z-Source Ultrasparse Matrix Converter", *Asian Journal of Applied science and Technology*, Volume 3, Issue 1, Pages 280-287, Jan-March 2019



Figure No: 1 Topology of Z-Source Ultrasparse Matrix Converter

The topology of the ZSUSMC, where X-molded impedance arranges is embedded between the rectifier and inverter phases of a USMC, is delineated in Fig. 1. In examination with customary IMC, which utilizes four switches and four diodes in every leg of the rectifier arrange, the USMC uses just a single switch and four diodes in every leg. This noteworthy preferred standpoint is accomplished to the detriment of losing the bidirectional power stream probability that exists in customary MCs. The structure of the inverter is like that of a two-level voltage source converter. Because of the nearness of the ZS arrange, the inverter can be worked at the shoot-through stage to help the info voltage.

This work aims to present a study of the development of a dynamic model based on theories of PI control and PID control and optimization to design voltage regulator circuit. The results of PI controller and PID controller are compared and the performance shows that PID is better than PI controller.

2. RELATED WORK

So as to address the restricted VTR issue in DMC and IMC, over modulation methodologies are proposed [1]. In spite of some achievement, these systems result in low-quality information flows and yield voltages. Different methodologies, for example, utilizing a stage up transformer at the yield terminals of the lattice converter or changing the topology have not gotten much consideration because of extra expenses and unpredictability.

Joining Z-source (ZS) systems with MC topologies is viewed as a feasible answer for upgrading the boosting ability of the MC [2]. An extensive audit of ZS systems utilized with DMC is completed in [3]. Due to the previously mentioned favorable circumstances of IMC over DMC, Z-source IMC (ZSIMC) is considered and examined in this work. In [4], ZS organize is recommended to be set between the three-stage input voltage source and the IMC. This course of action acknowledges high VTRs with little ZS segments; however, it expands the expense and diminishes the dependability of the converter because of extra switches in the structure. The execution of ZSIMC with three ZS designs is assessed as far as VTR, current and voltage swell, and weight on the switches.

3. EXISTING SYSTEM

3.1 PI Controller

PI controller will dispose the constrained motions and consistent state errors bring about an activity of on-off controller and P controller separately. Notwithstanding, presenting fundamental mode negatively affects the speed

of the reaction and generally steadiness of the framework. Subsequently, PI controller won't build the speed of reaction. It tends not out of the ordinary since the PI controller does not have intends to anticipate what will occur with the blunder in not so distant future. This issue can be explained by presenting subsidiary mode which has the capacity to foresee what will occur with the blunder in not so distant future and along these lines to diminish a response time of the controller [6]. PI controllers are regularly utilized in industry, particularly when the speed of the reaction isn't an issue. A control without D mode is utilized when:

a) quick reaction of the framework isn't required

b) extensive unsettling influences and clamor are available during the task of the procedure

c) there is just a single vitality stockpiling in the procedure (capacitive or inductive)

d) there are substantial transport delays in the framework

The block diagram of PI controller is shown in figure 2.



Figure No: 2 Block Diagram of PI Controller

3.2 Drawbacks of PI Controller

a) Integrator wind up phenomenon

Integral or Proportional + Integral controllers are not stable. When there is a limit on the actuation capability, the controller output saturates leading to non-decaying errors. The integrator blindly accumulates the error and its output can grow to large values.

b) Leads of Instability

Integral control leads to sluggish closed-loop response for a first order system. Integral control of higher order plants may lead to instability.

4. PROPOSED SYSTEM

PID controller has all the fundamental elements: quick response on change of the controller input (D mode), increment in control flag to lead blunder towards zero (I mode) and reasonable activity inside control mistake

territory to take out motions (P mode). Subordinate mode improves soundness of the framework and empowers increment in addition K and abatement in necessary time consistent T_i, which builds speed of the controller reaction. PID controller is utilized when managing higher request capacitive procedures (forms with more than one vitality stockpiling) when their dynamic isn't like the elements of an integrator (like in numerous warm procedures). PID controller is frequently utilized in industry, yet additionally in the control of versatile items (course and direction following included) when strength and exact reference following are required. Customary autopilot is generally PID type controllers [7].

Proportional Integral Derivative (PID) controllers are generally utilized in modern control frameworks on account of the decreased number of parameters to be tuned. They give control flags that are corresponding to the blunder between the reference flag and the real yield (relative activity), to the essential of the mistake (indispensable activity), and to the subordinate of the blunder (subsidiary activity), to be specific

$$u(t) = K_p \left[e(t) + \frac{1}{T_i} \int_0^t e(\tau)\, d\tau + T_d \frac{d}{dt} e(t) \right]$$

Where u(t) and e(t) denote the control and the error signals, respectively, and K_p, T_i and T_d are the parameters to be tuned. The corresponding transfer function is given as

$$K(s) = K_p \left(1 + \frac{1}{T_i s} + T_d s \right)$$

The fundamental highlights of PID controllers are the ability to dispense with consistent state blunder of the reaction to a stage reference flag (on account of necessary activity) and the capacity to foresee yield changes (when subsidiary activity is utilized).



Figure No: 3 Block Diagram of PID Controller

The most utilized PID structure strategy utilized in the business is the Ziegler– Nichols technique, which evades the requirement for a model of the plant to be controlled and depends entirely on the progression reaction of the plant. The parameter setting, as per the Ziegler– Nichols technique, is done in four stages.

1) Obtain the plant step reaction.

2) Draw the steepest straight-line digression to the reaction.

3) Obtain the measures α and L.

4) Set the parameters K_p, T_i and T_d.

The block diagram of PID controller is shown in figure 3.

It is outstanding that input frameworks with PID controllers tuned by the Ziegler– Nichols step reaction strategy have great unsettling influence dismissal. Nonetheless, the remunerated framework reaction to a stage flag has, when all is said in done, a high-percent overshoot, and the control flag is generally high, which may lead the actuator to immersion. In a few procedures, (for example, synthetic procedure), high-percent overshoot isn't an issue, giving that the framework returns quickly to the area of the enduring state esteem. Nonetheless, in different procedures, (for example, in the production of plastic gloves), it is alluring to have no overshoot by any means; subsequently, the Ziegler– Nichols strategy can't be utilized to tune PID controllers for these frameworks. Another limitation of Ziegler– Nichols is that it is reasonable for frameworks with monotonic advance reaction (S-shape reaction).

5. RESULTS AND DISCUSSION

In this work, tuning strategies for PI and PID controllers are proposed with the end goal that the reaction of the remunerated framework has overshoot underneath a recommended esteem. The approach likewise envelops the structure of PID controllers for plants with underdamped step reaction. All the advancement of the procedures is basic and depends entirely on ideas presented in a recurrence space based control course. The results of PI and PID controllers are shown below:



Figure No: 4 Full Model with PI controller

 Online ISSN: 2456-883X



Figure No: 5 VDC Voltage from Network



Figure No: 6 Voltage and Current from Inverter



Figure No: 7 Full Model with PID Controller

Online ISSN: 2456-883X



Figure No: 8 VDC of PID Module



Figure No: 9 Voltage and Current from Inverter

In PID controller executions, examining interims ought to be equivalent consistently. To show, if the position is changing at a steady rate yet the example time fluctuates from test to test, the framework will get commotion on the differential term. On the off chance that the differential addition is high this commotion will be enhanced a lot. In this way, some technique to avert uneven example rates must be used. Now, TIMER hinders of the PIC microcontrollers would be very helpful since the PID capacity can be called from the Interrupt Service Routine (ISR) with equivalent time interims.

6. CONCLUSION

A large portion of the modern controllers are P-I-D in nature. The real purposes for the notoriety of P-I-D controller are its straightforwardness in structure and the materialness to assortment of procedures. In addition the controller

can be tuned for a procedure, even without detailed numerical model of the procedure. Be that as it may, appropriate tuning of the controller parameters requires broad experimentation. The strategies for controller tuning would be talked about in the following exercise. Roughly, the ideal closed circle exhibitions, for example, quick reaction, zero consistent state mistakes and less overshoot are accomplished through fuse of P, I and D activities separately. Be that as it may, the decision of P-D, P-I or P-I-D structure relies upon the kind of the procedure we plan to control.

7. REFERENCES

[1] A. M. Bozorgi, M. Monfared, and H. Mashhadi, "Two simple overmodulation algorithms for space modulated three-phase to three-phase matrix converter," IET Power Electron., vol. 7, no. 7, pp. 1915–1924, Jul. 2014.

[2] Y. P. Siwakoti, F. Z. Peng, F. Blaabjerg, P. C. Loh, and G. E. Town, "Impedance-source networks for electric power conversion Part I: A topological review," IEEE Trans. Power Electron., vol. 30, no. 2, pp. 699–716, Feb. 2015.

[3] B. Ge, Q. Lei, W. Qian, and F. Z. Peng, "A family of Z-source matrix converters," IEEE Trans. Ind. Electron., vol. 59, no. 1, pp. 35–46, Jan. 2012.

[4] S. Liu, B.Ge, H. Abu-Rub, and F. Z. Peng, "Modeling, analysis, and motor drive application of quasi-Z-source indirect matrix converter," COMPEL: Int. J. Comput. Math. Electr. Electron. Eng., vol. 33, no. 1/2, pp. 28–28, 2013.

[5] E. Karaman, M. Farasat, and A. M. Trzynadlowski, "A comparative study of series and cascaded Z-source matrix converters," IEEE Trans. Ind. Electron., vol. 61, no. 10, pp. 5164–5173, Oct. 2014.

[6] Xiao, W.D&D.Y.Xue, 'Desgin for PID controller toolbox based on MATLAB/ simulation', Northeastern University, 2004, pp: 20-25.

[7] C. C. Hang, K. J. Astrom, and W. K. Ho, "Refinements of the Ziegler–Nichols tuning formula," Proc Inst. Elect. Eng.—Part D: Control Theory and Applications, vol. 138, no. 2, pp. 111–118, 1991.